

**SLIK**<sup>®</sup>

Designed and engineered in Japan



# PRODUCT CATALOG

SUPPORTING  
THE ART OF  
IMAGE-MAKING

[www.slik.com/](http://www.slik.com/)

2018.9

SLIK has been quietly designing and manufacturing high-quality tripods for more than 60 years. SLIK has won 6 prestigious Japanese Ministry of International Trade and Industry (MITI) awards for its original and innovative designs, which have become industry standards. Check out the quality and heritage of SLIK tripods, monopods and heads thru online.

**1948 BIRTH OF SLIK TRIPOD**

Mr. Takatoshi Shiraishi, a mechanical engineer and photography enthusiast, began designing and creating his own tripods by himself in the suburb of Tokyo, Japan when he was 23 years old.

The first brand name was "ALPS" and then, it had been changed to "SLICK" in the beginning of 1950s.



**1956 INCORPORATION OF A COMPANY**

Mr. Shiraishi founded SLICK Elevator Tripod Co., Ltd. and at the same time, SLICK introduced "SLICK Master" tripod for professional and press photographers especially.

**1963 CHANGE OF COMPANY NAME**

The company name was changed to SLICK Tripod Co., Ltd. SLICK introduced a unique multi-action head which could get any angles with one pan handle.

**1967 CONSTRUCTION OF NEW HIDAKA FACTORY**

The "Hidaka" factory was constructed newly in Saitama Prefecture, Japan for the mass production. SLICK "Master Deluxe" and SLICK "Goodman Ace" tripods received "Good Design Awards" (G-Mark) by The Ministry of International Trade and Industry (MITI) of Japan.

SLICK Tripod Sales Co., Ltd. was created as a separate business entity from SLICK Tripod Co., Ltd. to focus exclusively on sales of the products.

**1974 NEW SLIK LOGO**

The letter of "SLICK" in our company name was changed to "SLIK".

**1977 MULTI-FUNCTION SYSTEM**

SLIK started to sell the new model "88M" tripod, which has various functions that are commonplace today, such as the simple movement from low position to high position, lever leg locks, quick release shoe system, etc. It received "Good Design Award" (G-Mark) by The MITI of Japan in this year.

**1987 SLIK AMERICA, INC.**

SLIK America, Inc. was established in New York, U.S.A. for the sales in U.S. market.

**1988 SLIK (THAILAND) CO., LTD**

Slik (Thailand) Co., Ltd. was established and a factory constructed in the suburb of Bangkok, Thailand to meet the increasing demands for good quality inexpensive tripods without using any outside manufacturing.

The unique trigger style Ball Head "AF2100" received "Good Design Award" (G-Mark) by The MITI of Japan.

**1989 SLIK CORPORATION**

Slik Tripod Sales Co., Ltd. merged back into Slik Tripod Co., Ltd. and the single company was named SLIK CORPORATION.

**1994 U-SERIES TRIPODS**

SLIK tripod model "U 8000" (made in Thailand factory) received "Good Design Awards" (G-Mark) by The MITI of Japan.

History of SLIK Tripods

1948



1950

ALPS Tripods

1956



1950

1956

SLICK J


SLICK MASTER (First version)

1960



Updated SLICK Master

1967



Goodman Ace / Master Deluxe

1972



Goodman S-104

Master Pro II

than 60 years.  
 (MITI) “Good Design” (G-Mark) awards.

and at your local camera stores.

**1997 NEW BALL HEAD & A.M.T. TRIPODS**

SLIK “Ball Head 800” (made in Thailand factory) received “Good Design Awards” (G-Mark) by The MITI of Japan. Introduction of the new alloy of SLIK A.M.T. (Aluminum, Magnesium and Titanium) and then, started sales of our tripod model “PRO 700DX” and monopod “PRO POD 600” using this new alloy in the legs.

**1999 CARBON FIBER PRODUCTS**

Began the production and sales of new Carbon Fiber tripod model “PRO 803CF”, “PRO 804CF” and monopod “PRO POD 380”.

**2001 NEW SLIK**

Became a member of Kenko Co., Ltd. (now, Kenko Tokina Co., Ltd.).

**2012 THE 2nd FACTORY IN THAILAND**

The 2nd factory in Thailand was opened at Saraburi, Thailand after the heavy damage by large-scale flood at the original first factory at Navanakorn in 2011.

**2014 SLIK BLUE**

SLIK decided to make the image color of the product BLUE. Since then, SLIK BLUE has been adopted as the accent color of the product.



**2016 R.F.M (Rapid Flip Mechanism)**

SLIK original travel tripod; LiTE series had been introduced at Photokina 2016. SLIK patented “R.F.M.” eases inverting tripod legs for compact storage.

**2018 TO THE NIGHTLY SKY & TIME-LAPSE**

SLIK expands product range to the astronomical photography. ASTRA sky tracker is the ideal piece for not only astronomical photography but also unique time-lapse shooting.

**Contents**

Carbon Fiber Series ..... 04  
 LiTE Series ..... 08  
 Pro Series ..... 09  
 HD Series ..... 12  
 EZ Series ..... 12  
 Sprint Series ..... 13  
 U Series ..... 14  
 Compact & Mini Series ..... 14  
 Mémoire Series ..... 14  
 Video Series ..... 15  
 Heads ..... 16  
 Monopods ..... 20  
 Accessories ..... 21  
 Specification Chart ..... 23

**Key to Symbols**

**Load Capacity**

---

**Maximum Height**  
 A: Maximum height of tripod with the tripod center column and legs fully extended.  
 B: Maximum height of tripod with legs fully extended but the center column not raised.

---

**Minimum Height**  
 The lowest operational height of tripod with legs fully spread and the center column in lowest position.

---

**Folded Length**  
 The minimum folded length of the tripod.

---

**Weight**

---

**Quick Release Type**

---

**Shape of leg pipe / tube and diameter of the first upper leg.**



## Heavy-duty & Large type

**MADE IN JAPAN**



### Worm gear

It operates up and down when operating the handle. It corresponds to the weight equipment because they do not own weight fall.



### Japan made of Carbon Fiber pipes

Using high-grade and high-quality Japanese-made Carbon Fiber pipes. It boasts excellent high stability in rigidity.



### 2-way leg-tip

In such rocky enables setting of thing in stable tripod using a spike.

Full-size/APS-C SLR + Super-telephoto lens

Medium format + Telephoto lens

8x10-4x5 format/Studio shot

## GRAND PRO CF-4

36mm 4-section Carbon Fiber

U1/4-U3/8 Head mounting screw Three-steps leg opening

Load Capacity 14kg  
 Height A: 2,540mm B: 2,255mm  
 Leg length 450mm  
 Weight 3,800g  
 Height 825mm



### Optional short center column (for Professional II-LE)

Exchanging the standard center column and then, you will get lower position. (see page No.21)



### Head mounting screw

Corresponding to both U1/4 and U3/8 head mounting screws.



### Rack-and-pinion type center column

Convenient rack-and-pinion type center column in fine adjustment of the height. Friction adjustment with function.



### 3-steps leg angle adjustment

Leg angle adjustable from a high position to a low position.



### A.R.S. (Anti-Rotation System)

The A.R.S. systems prevent the leg tubes from rotating inside each other making it much easier to lock and release all the twist-release locks securely.



### Leg lock system (crown-type) (PAT.)

Twist lock system with double nut ring crown type (PAT.).



### Exchangeable leg tips

Leg tips can be exchanged to spike leg tips from rubber leg tips. \* SPIKE SET is sold separately as an optional.

Full-size/APS-C SLR + 300mm F2.8 class

Medium format + Telephoto lens

4x5 format field camera

## PRO 924CF

32mm 4-section Carbon Fiber

U1/4-U3/8 Head mounting screw Three-steps leg opening A.R.S. Anti-Rotation System

Load Capacity 10kg  
 Height A: 1,790mm B: 1,480mm  
 Leg length 180mm  
 Height 554mm  
 Weight 2,310g



Short center column attached as standard

## PRO 923CF

32mm 3-section Carbon Fiber

U1/4-U3/8 Head mounting screw Three-steps leg opening A.R.S. Anti-Rotation System

Load Capacity 10kg  
 Height A: 1,900mm B: 1,590mm  
 Leg length 215mm  
 Height 708mm  
 Weight 2,320g



Short center column attached as standard

**SPIKE SET** P.21

## Recommendable 3-way Pan Heads



SH-909



SH-908

## Recommendable 3-way Pan Heads



SH-807E

with Quick Release Shoe



SH-806E

with Quick Release Shoe

	Bubble level	Size of camera platform	Camera mounting screw	Tripod mounting screw	Height	Weight	Load capacity
SH-909	Dual axis bubble level	82x90mm	U1/4-U3/8	U3/8	140mm	1,710g	12kg
SH-908	Dual axis bubble level	72x71mm	U1/4-U3/8	U3/8	135mm	1,410g	10kg
SH-807E	Dual axis bubble level plus single bubble level	57x59mm	U1/4	U3/8	150mm	1,000g	10kg
SH-806E	Dual axis bubble level plus single bubble level	57x59mm	U1/4	U1/4	134mm	700g	7kg

## Medium type



### Head mounting screw

Corresponding to both U1/4 and U3/8 head mounting screws.



### 3-steps leg angle adjustment

Leg angle adjustable from a high position to a low position.



### A.R.S. (Anti-Rotation System)

The A.R.S. systems prevent the leg tubes from rotating inside each other making it much easier to lock and release all the twist-release locks securely.



### Leg lock system (crown-type) (PAT.)

Twist lock system with double nut ring crown type (PAT.).



### The hook at the bottom of the center column

Accessory hook capable of suspending a weight.



### Exchangeable leg tips

Leg tips can be exchanged to spike leg tips from rubber leg tips. "SPIKE SET" is sold separately as an optional.

-  Full-size SLR + 70-200mm F2.8 class
-  APS-C SLR + 70-200mm F2.8 class
-  Medium format + Standard lens





**NEW**

## PRO CF-834



 28mm 4-section **Carbon Fiber**

**U1/4-U3/8** Head mounting screw **Three-steps** leg opening **A.R.S.** Anti-Rotation System  
**Crown-cap** Leg lock system **Accessory** hook **Exchangeable** leg tips

Load Capacity 7kg  A: 1,650mm B: 1,325mm  
 190mm  480mm  
 1,560g







**NEW**

## PRO CF-833



 28mm 3-section **Carbon Fiber**

**U1/4-U3/8** Head mounting screw **Three-steps** leg opening **A.R.S.** Anti-Rotation System  
**Crown-cap** Leg lock system **Accessory** hook **Exchangeable** leg tips

Load Capacity 7kg  A: 1,710mm B: 1,385mm  
 235mm  600mm  
 1,550g




**SPIKE SET**  P.21

## Recommendable Heads



**SH-837HD**  P.16

Best for D-Movie 



**AF2100**  P.18

with Quick Release Shoe

 Won the Good Design Long Life Design Award



**SBH-808DQ**  P.17

with Quick Release Shoe

	Bubble level	Size of camera platform	Camera mounting screw	Tripod mounting screw	Height	Weight	Load capacity
SH-837HD	Dual axis bubble level plus single bubble level	57x76mm	U1/4	U3/8	120mm	1,020g	7kg
AF2100	Single bubble level	41x47mm	U1/4	U1/4-U3/8	140mm	870g	3kg
SBH-808DQ	-	50x50mm	U1/4	U1/4-U3/8	120mm	760g	5kg

# Carbon Fiber Series



**Head mounting screw**  
Corresponding to both U1/4 and U3/8 head mounting screws.



**3-steps leg angle adjustment**  
Leg angle adjustable from a high position to a low position.



**A.R.S. (Anti-Rotation System)**  
The A.R.S. systems prevent the leg tubes from rotating inside each other making it much easier to lock and release all the twist-release locks securely.



**Leg lock system (crown-type) (PAT.)**  
Twist lock system with double nut ring crown type (PAT.).



**The hook at the bottom of the center column**  
Accessory hook capable of suspending a weight.



**Exchangeable leg tips**  
Leg tips can be exchanged to spike leg tips from rubber leg tips. "SPIKE SET" is sold separately as an optional.

## Medium type

- Full-size SLR + 70-200mm F2.8 class
- APS-C SLR + 70-200mm F2.8 class
- Medium format + Standard lens

### NEW PRO CF-734

25mm 4-section Carbon Fiber

U1/4-U3/8 Head mounting screw Three-steps leg opening  
A.R.S. Anti-Rotation System crown-cap Leg lock system  
Accessory hook Exchangeable leg tips

Load Capacity 5kg  
A: 1,650mm B: 1,325mm  
180mm  
475mm  
1,350g



### NEW PRO CF-733

25mm 3-section Carbon Fiber

U1/4-U3/8 Head mounting screw Three-steps leg opening  
A.R.S. Anti-Rotation System crown-cap Leg lock system  
Accessory hook Exchangeable leg tips

Load Capacity 5kg  
A: 1,675mm B: 1,320mm  
210mm  
575mm  
1,330g



**SPIKE SET** P.21

## Light Weight type

- D-SLR
- Mirror-less SLR
- Digital Movie

### NEW PRO CF-634

22mm 4-section Carbon Fiber

U1/4-U3/8 Head mounting screw Three-steps leg opening A.R.S. Anti-Rotation System  
crown-cap Leg lock system Accessory hook

Load Capacity 3kg  
A: 1,590mm B: 1,310mm  
105mm  
475mm  
930g



### NEW PRO CF-633

22mm 3-section Carbon Fiber

U1/4-U3/8 Head mounting screw Three-steps leg opening A.R.S. Anti-Rotation System  
crown-cap Leg lock system Accessory hook

Load Capacity 3kg  
A: 1,630mm B: 1,240mm  
125mm  
540mm  
900g



### NEW PRO CF-635

22mm 5-section Carbon Fiber

U1/4-U3/8 Head mounting screw Three-steps leg opening A.R.S. Anti-Rotation System  
crown-cap Leg lock system Accessory hook

Load Capacity 3kg  
A: 1,310mm B: 1,120mm  
90mm  
370mm  
870g



## Recommendable Heads



**NEW**  
Best for D-Movie

**SH-737HD** P.16  
with Quick Release Shoe



**SH-726E** P.16  
with Quick Release Shoe



**SH-707E** P.18  
with Quick Release Shoe



**AF1100E** P.18  
with Quick Release Shoe



**NEW**  
ARCA-SWISS Compatible Q.R.S.

**PBH-635AS** P.17  
with Quick Release Shoe

	Bubble level	Size of camera platform	Camera mounting screw	Tripod mounting screw	Height	Weight	Load capacity
SH-737HD	Single bubble level	50x76mm	U1/4	U1/4	105mm	650g	5kg
SH-726E	Single bubble level	56x52mm	U1/4	U1/4	104mm	580g	5kg
SH-707E	Dual axis bubble level	48x36mm	U1/4	U1/4	81mm	470g	5kg
AF1100E	Single bubble level	48x36mm	U1/4	U1/4	125mm	540g	1.5kg
PBH-635AS	Single bubble level	38x63mm	U1/4	U1/4-U3/8	102mm	484g	6kg



**Head mounting screw**  
Corresponding to both U1/4 and U3/8 head mounting screws.



**3-steps leg angle adjustment**  
Leg angle adjustable from a high position to a low position.



**A.R.S. (Anti-Rotation System)**  
The A.R.S. systems prevent the leg tubes from rotating inside each other making it much easier to lock and release all the twist-release locks securely.



**Leg lock system (crown-type) (PAT.)**  
Twist lock system with double nut ring crown type (PAT.).



**The hook at the bottom of the center column**  
Accessory hook capable of suspending a weight.



**Exchangeable leg tips**  
Leg tips can be exchanged to spike leg tips from rubber leg tips. "SPIKE SET" is sold separately as an optional.

## Mediume type

- Full-size SLR + 70-200mm F2.8 class
- APS-C SLR + 70-200mm F2.8 class
- Medium format + Standard lens

**NEW**

### PRO CF-834BH6

ARCA-SWISS Compatible Q.R.S.



with ball head PBH-635AS

28mm 4-section Carbon Fiber

- U1/4-U3/8 Head mounting screw
- Three-steps leg opening
- A.R.S. Anti-Rotation System
- crown-top Leg lock system
- Accessory hook
- Exchangeable leg tips

- Load Capacity: 6kg
- Height: A:1,752mm B:1,427mm
- Width: 292mm
- Height: 566mm
- Weight: 2,040g
- Q.R.S.: 6507 Q.R.S.



**NEW**

### PRO CF-833BH6

ARCA-SWISS Compatible Q.R.S.



with ball head PBH-635AS

28mm 3-section Carbon Fiber

- U1/4-U3/8 Head mounting screw
- Three-steps leg opening
- A.R.S. Anti-Rotation System
- crown-top Leg lock system
- Accessory hook
- Exchangeable leg tips

- Load Capacity: 6kg
- Height: A:1,812mm B:1,487mm
- Width: 337mm
- Height: 686mm
- Weight: 2,030g
- Q.R.S.: 6507 Q.R.S.



**SPIKE SET** P.21

## Mediume type

- Full-size SLR + 70-200mm F2.8 class
- APS-C SLR + 70-200mm F2.8 class
- Medium format + Standard lens

**NEW**

### PRO CF-734BH5

ARCA-SWISS Compatible Q.R.S.



with ball head PBH-535AS

25mm 4-section Carbon Fiber

- U1/4-U3/8 Head mounting screw
- Three-steps leg opening
- A.R.S. Anti-Rotation System
- crown-top Leg lock system
- Accessory hook
- Exchangeable leg tips

- Load Capacity: 5kg
- Height: A:1,747mm B:1,422mm
- Width: 277mm
- Height: 557mm
- Weight: 1,730g
- Q.R.S.: 6507 Q.R.S.



**NEW**

### PRO CF-733BH5

ARCA-SWISS Compatible Q.R.S.



with ball head PBH-535AS

25mm 3-section Carbon Fiber

- U1/4-U3/8 Head mounting screw
- Three-steps leg opening
- A.R.S. Anti-Rotation System
- crown-top Leg lock system
- Accessory hook
- Exchangeable leg tips

- Load Capacity: 5kg
- Height: A:1,772mm B:1,417mm
- Width: 307mm
- Height: 657mm
- Weight: 1,710g
- Q.R.S.: 6507 Q.R.S.



**SPIKE SET** P.21

## Recommendable 3-way Pan Heads

### LIGHT WEIGHT

Constructed from cast Aluminum, designed for fitting carbon fiber tripods.

### RUBBER COATED PAN HANDLES (SH-704E only)

Easy grip rubber handles for precise positioning.

	Bubble level	Size of camera platform	Camera mounting screw	Tripod mounting screw	Height	Weight	Load capacity
SH-705E	—	54x47mm	U1/4	U1/4	90mm	450g	5kg
SH-704E	Single bubble level	48x36mm	U1/4	U1/4	75mm	290g	3kg



**SH-705E** P.16  
with Quick Release Shoe



**SH-704E** P.16  
with Quick Release Shoe

## Light Weight type

-  D-SLR
-  Mirror-less SLR
-  Digital Movie



**R.F.M** Rapid Flip Mechanism  
Quick and easy leg angle adjustment and collapse.



**LED LIGHT**  
Integrated LED light in center column for shooting in the dark.



**Rubber grip of the 3-D molding**  
Easy to hold and no penetration of water even in rainy weather, etc. (except for AL-420S)

## CARBON FIBER LEGS



**ARCA-SWISS compatible**  
New high precision ball head SBH-180DS with ARCA-SWISS compatible quick release shoe.



**7-layers ARS carbon fiber pipes**  
Made by special extruding machines and higher rigidity than 8-10 layers' carbon fiber pipes made by hand-rolling.



**Leg lock system (crown-type) (PAT.)**  
Twist lock system with double nut ring crown type (PAT.).



**EXCLUSIVE BAG**

### LiTE CF-522

ARCA-SWISS Compatible Q.R.S.

with ball head SBH-180DS

22mm 5-section Carbon Fiber

Three-steps leg opening, A.R.S. Anti Rotation System, crown-cap Leg lock system, Accessory hook

Load Capacity: 3kg, Max. height: A:1,466mm, B:1,217mm, Leg length: 187mm, Max. width: 370mm, Weight: 1,113g (including batteries), Q.R.S.: 6502



### LiTE CF-422

ARCA-SWISS Compatible Q.R.S.

with ball head SBH-180DS

22mm 4-section Carbon Fiber

Three-steps leg opening, A.R.S. Anti Rotation System, crown-cap Leg lock system, Accessory hook

Load Capacity: 3kg, Max. height: A:1,782mm, B:1,427mm, Leg length: 196mm, Max. width: 473mm, Weight: 1,178g (including batteries), Q.R.S.: 6502



## ALUMINUM LEGS



**Adopting a one-touch quick release shoe type**

Equipped with a dedicated camera platform, which was long the connection of the camera platform and the ball portion.



**Lever-type leg lock system**

Easy and fast for leg opening & closing.

### LiTE AL-420

with ball head SBH-100DQA

20mm 4-section Aluminum

Three-steps leg opening, Accessory hook

Load Capacity: 2kg, Max. height: A:1,534mm, B:1,309mm, Leg length: 170mm, Max. width: 428mm, Weight: 1,015g (including batteries), Q.R.S.: 6252



### LiTE AL-420M

with ball head SBH-100DQA

20mm 4-section Aluminum

Three-steps leg opening, Accessory hook

Load Capacity: 2kg, Max. height: A:1,241mm, B:1,070mm, Leg length: 165mm, Max. width: 358mm, Weight: 930g (including batteries), Q.R.S.: 6252



### LiTE AL-420S

with ball head SBH-100DQA

20mm 4-section Aluminum

Three-steps leg opening, Accessory hook

Load Capacity: 2kg, Max. height: A:1,014mm, B:890mm, Leg length: 158mm, Max. width: 310mm, Weight: 785g (including batteries), Q.R.S.: 6252



### Be a 500cc PET bottle

When folded, becoming the same size as 500cc PET bottle because of especially designed head and it fits between legs.

	Max. height	Folded length	Weight	Leg Section
CF-522	1,466mm	370mm	1,113g	5
CF-422	1,782mm	473mm	1,178g	4
AL-420S	1,014mm	310mm	785g	4
AL-420M	1,241mm	358mm	930g	4
AL-420	1,534mm	428mm	1,015g	4



# PROFESSIONAL Series

Designed with the professional photographer in mind. Ultra heavy construction for use with D-SLR and 35mm still camera with long telephoto/zoom lens, large format camera and medium format camera.

Heavy-duty & Large type

**MADE IN JAPAN**

- Full-size/APS-C SLR + Super-telephoto lens
- Medium format + Telephoto lens
- 8x10-4x5 format/Studio shot

## THE PROFESSIONAL

Heavy duty construction. 3-way pan head provides ultra-smooth camera movement. Adjustable camera mounting screw for both 1/4" and 3/8". Dual axis bubble level for precise horizontal positioning. Grooved tubular legs allow you to extend legs quickly and easily. Worm gear elevation control for precise height setting. 100mm indexed reference marks on the second leg section for precise leg alignment.



### Worm gear

It operates up and down when operating the handle. It corresponds to the weight equipment because they do not own weight fall.



### 3-steps leg angle adjustment

Leg angle adjustable from a high position to a low position.



### Grooved pipes

Possible to pipe each other to stretch smoothly without idling.



### Camera mounting screw (corresponding both U1/4 and U3/8 screws)

Housing an U3/8 screw into the camera platform.



## THE PROFESSIONAL 4

with high precision 3-way pan head SH-909



36mm 4-section Aluminum

Load Capacity	12kg	A	2,530mm	B	2,250mm
Min. height	590mm	Max. height	935mm		
Weight	6,810g				



## THE PROFESSIONAL

with high precision 3-way pan head SH-909



36mm 3-section Aluminum

Load Capacity	12kg	A	2,000mm	B	1,720mm	Min. height	590mm
Max. height	900mm	Weight	6,210g				



## PROFESSIONAL II-LE

with high precision 3-way pan head SH-908



32mm 3-section Aluminum

Load Capacity	10kg	A	1,835mm	B	1,550mm	Min. height	585mm
Max. height	810mm	Weight	4,810g				

One size smaller The Professional for the shooting in the outdoors. Equipped with a urethane soft grip.

### Optional short center column for The Professional series

### Optional short center column for Professional II-LE

Exchanging the standard center column and then, you will get lower position. (see page No.21)



## Legs

36mm 4-section Aluminum



### THE PROFESSIONAL 4 LEG

36mm 3-section Aluminum



### THE PROFESSIONAL LEG


32mm 3-section Aluminum



### PROFESSIONAL II-LE LEG

	Head attachment screw	Max. operating height	Min. operating height	Folded length	Weight
THE PROFESSIONAL 4 LEG	U1/4 · U3/8	2,390mm	450mm	795mm	5,100g
THE PROFESSIONAL LEG	U1/4 · U3/8	1,860mm	450mm	760mm	4,500g

	Head attachment screw	Max. operating height	Min. operating height	Folded length	Weight
PROFESSIONAL II-LE LEG	U1/4 · U3/8	1,700mm	450mm	675mm	3,400g



**SLIK Super Alloy A. M. T.**  
A.M.T. alloy has a 40% greater strength to weight ratio than standard aluminum, meaning the legs are lighter weight yet stronger than the standard metal used in most of today's tripods.



**Head mounting screw**  
Corresponding to both U1/4 and U3/8 head mounting screws.



**3-steps leg angle adjustment**  
Leg angle adjustable from a high position to a low position.



**Lever-type leg lock**  
Robust leg lock system that can operate quickly and easily.



**Plastic lever-type leg lock**  
Compact and light-weight plastic leg lock.

## Heavy-duty type

- Full-size/APS-C SLR + 300mm F2.8 class
- Medium format + Telephoto lens
- 4x5 format field camera

### PRO 700DX

with 3-way pan head PRO 700DX HEAD



30.2mm 3-section A.M.T. Aluminum-Magnesium-Titanium alloy

U1/4-U3/8 Head mounting screw Three-steps leg opening lever-type leg lock

- Load Capacity: 8kg
- Height: A: 1,900mm B: 1,520mm
- Leg length: 395mm
- Min. height: 760mm
- Weight: 3,670g
- Q.R.S: 6124 Q.R.S, 6125 Q.R.S



## Medium type

- Full-size SLR + 70-200mm F2.8 class
- APS-C SLR + 70-200mm F2.8 class
- Medium format + Standard lens

### PRO 500DX

with 3-way pan head ABLE 300DX HEAD



26.8mm 3-section A.M.T. Aluminum-Magnesium-Titanium alloy

U1/4-U3/8 Head mounting screw Three-steps leg opening lever-type leg lock

- Load Capacity: 6kg
- Height: A: 1,645mm B: 1,385mm
- Leg length: 350mm
- Min. height: 695mm
- Weight: 2,730g
- Q.R.S: 6123 Q.R.S



**NEW**

### PRO 700BH6

ARCA-SWISS Compatible Q.R.S.



with ball head PBH-635AS

30.2mm 3-section A.M.T. Aluminum-Magnesium-Titanium alloy

U1/4-U3/8 Head mounting screw Three-steps leg opening lever-type leg lock

- Load Capacity: 6kg
- Height: A: 1,882mm B: 1,502mm
- Leg length: 377mm
- Min. height: 766mm
- Weight: 3,150g
- Q.R.S: 6507 Q.R.S



**NEW**

### PRO 500BH5

ARCA-SWISS Compatible Q.R.S.



with ball head PBH-535AS

26.8mm 3-section A.M.T. Aluminum-Magnesium-Titanium alloy

U1/4-U3/8 Head mounting screw Three-steps leg opening lever-type leg lock

- Load Capacity: 5kg
- Height: A: 1,642mm B: 1,382mm
- Leg length: 347mm
- Min. height: 707mm
- Weight: 2,460g
- Q.R.S: 6507 Q.R.S



## Legs

30.2mm 3-section A.M.T. Aluminum-Magnesium-Titanium alloy

### PRO 700DX LEG



## Legs

26.8mm 3-section A.M.T. Aluminum-Magnesium-Titanium alloy

### PRO 500DX LEG



	Head attachment screw	Max. operating height	Min. operating height	Folded length	Weight
<b>PRO 700DX LEG</b>	U1/4 · U3/8	1,780mm	275mm	680mm	2,670g
<b>PRO 500DX LEG</b>	U1/4 · U3/8	1,545mm	250mm	625mm	2,080g

- APS-C SLR + 70-300mm Zoom
- Digital Movie
- Mirror-less SLR

## PRO 330DX

with 3-way pan head SH-705E

23.4mm 4-section  
A.M.T. Aluminum-Magnesium-Titanium alloy  
U1/4-U3/8 Head mounting screw  
Three-steps leg opening  
Plastic lever-type leg lock

Load Capacity 3kg  
A: 1,592mm  
B: 1,242mm  
294mm

600mm  
1,705g  
6123 Q.R.S



## PRO 340DX

with 3-way pan head SH-705E

23.4mm 4-section  
A.M.T. Aluminum-Magnesium-Titanium alloy  
U1/4-U3/8 Head mounting screw  
Three-steps leg opening  
Plastic lever-type leg lock

Load Capacity 3kg  
A: 1,440mm  
B: 1,150mm  
258mm

490mm  
1,625g  
6123 Q.R.S



## PRO 340BH

with ball head SBH-200DQ

23.4mm 4-section  
A.M.T. Aluminum-Magnesium-Titanium alloy  
U1/4-U3/8 Head mounting screw  
Three-steps leg opening  
Plastic lever-type leg lock

Load Capacity 3kg  
A: 1,437mm  
B: 1,147mm  
255mm

515mm  
1,525g  
6183 Q.R.S



## PRO 340BH5

with ball head PBH-535AS

23.4mm 4-section  
A.M.T. Aluminum-Magnesium-Titanium alloy  
U1/4-U3/8 Head mounting screw  
Three-steps leg opening  
Plastic lever-type leg lock

Load Capacity 3kg  
A: 1,447mm  
B: 1,157mm  
265mm

507mm  
1,540g  
6507 Q.R.S



## PRO 330AF

with AF1100E

23.4mm 3-section  
A.M.T. Aluminum-Magnesium-Titanium alloy  
U1/4-U3/8 Head mounting screw  
Three-steps leg opening  
Plastic lever-type leg lock

Load Capacity 1.5kg  
A: 1,627mm  
B: 1,277mm  
329mm

660mm  
1,795g  
6183 Q.R.S



## Legs

23.4mm 3-section  
A.M.T. Aluminum-Magnesium-Titanium alloy

PRO 330DX LEG



23.4mm 4-section  
A.M.T. Aluminum-Magnesium-Titanium alloy

PRO 340DX LEG



	Head attachment screw	Max. operating height	Min. operating height	Folded length	Weight
PRO 330DX LEG	U1/4 · U3/8	1,502mm	204mm	535mm	1,255g
PRO 340DX LEG	U1/4 · U3/8	1,350mm	168mm	425mm	1,175g

# ABLE Series

## Medium type

- Full-size SLR + 70-200mm F2.8 class
- APS-C SLR + 70-300mm Zoom
- Digital Movie
- Mirror-less SLR



**Head mounting screw**  
Corresponding to both U1/4 and U3/8 head mounting screws.



**3-steps leg angle adjustment**  
Leg angle adjustable from a high position to a low position.



**Lever-type leg lock**  
Robust leg lock system that can operate quickly and easily. (PRO 400DX only)

## PRO 400DX

with 3-way pan head SH-705E

27mm 3-section  
U1/4-U3/8 Head mounting screw  
Three-steps leg opening  
Lever-type leg lock

Load Capacity 5kg  
A: 1,535mm  
B: 1,270mm  
590mm  
650mm  
2,520g  
6123 Q.R.S



## ABLE 300DX

with 3-way pan head ABLE 300DX HEAD

27mm 3-section  
U1/4-U3/8 Head mounting screw  
Three-steps leg opening

Load Capacity 5kg  
A: 1,550mm  
B: 1,285mm  
470mm  
655mm  
2,600g  
6123 Q.R.S



## Legs

27mm 3-section

PRO 400DX LEG



27mm 3-section

ABLE 300DX LEG



	Head attachment screw	Max. operating height	Min. operating height	Folded length	Weight
PRO 400DX LEG	U1/4 · U3/8	1,445mm	240mm	580mm	2,070g
ABLE 300DX LEG	U1/4 · U3/8	1,450mm	370mm	585mm	1,950g

# HD Series High definition series tripod.

## Medium type

- APS-C SLR + 70-300mm Zoom
- Digital Movie
- Mirror-less SLR

## HIGH DEFINITION SERIES TRIPODS

These tripods equip special 3-way pan head with oil fluid system. Pan and tilt frictions are adjusted by knobs easily. These tripods are the best for D-SLR with D-movie, yet suitable for D-SLR camera.

**NEW**

### PRO 500 HDII

with 3-way pan head SH-737HD

- 28.8mm 3-section
- A.M.T. Aluminum-Magnesium-Titanium alloy
- U1/4-US/B Head mounting screw
- Three-steps leg opening
- Plastic level-type leg lock

- Load Capacity: 5kg
- A: 1,650mm B: 1,390mm
- 355mm
- 710mm
- 2,730g
- 6264 Q.R.S



Best for D-Movie

**NEW**

### PRO 340 HDII

with 3-way pan head SH-737HD

- 23.4mm 4-section
- A.M.T. Aluminum-Magnesium-Titanium alloy
- U1/4-US/B Head mounting screw
- Three-steps leg opening
- Plastic level-type leg lock

- Load Capacity: 3kg
- A: 1,455mm B: 1,165mm
- 273mm
- 507mm
- 1,810g
- 6264 Q.R.S



Best for D-Movie

**NEW**

### PRO 330 HDII

with 3-way pan head SH-737HD

- 23.4mm 3-section
- A.M.T. Aluminum-Magnesium-Titanium alloy
- U1/4-US/B Head mounting screw
- Three-steps leg opening
- Plastic level-type leg lock

- Load Capacity: 3kg
- A: 1,607mm B: 1,257mm
- 309mm
- 615mm
- 1,905g
- 6264 Q.R.S



Best for D-Movie

# EZ Series Multi-action head series tripods.

## Medium type

- Full-size SLR + 70-200mm F2.8 class
- APS-C SLR + 70-300mm Zoom
- Digital Movie

## MULTI-ACTION HEAD SERIES TRIPODS

These tripods have the unique "Multi-action" head which allows easy operation with a single pan-tilt handle for D-SLR especially. It gives you the opportunity to pan and tilt simultaneously or individually and this permits you to take pictures at any desired angle.

### MASTER CLASSIC

with multi-action head MASTER CLASSIC HEAD

- 28mm 3-section
- Aluminum

- Load Capacity: 6kg
- A: 1,630mm B: 1,495mm
- 650mm
- 2,550g



### PRO 330EZ

with multi-action head SH-707E

- 23.4mm 3-section
- A.M.T. Aluminum-Magnesium-Titanium alloy
- U1/4-US/B Head mounting screw
- Three-steps leg opening
- Plastic level-type leg lock

- Load Capacity: 3kg
- A: 1,583mm B: 1,233mm
- 285mm
- 600mm
- 1,725g
- 6183 Q.R.S



**NEW**

### SPRINT PRO III EZ

with multi-action head SH-707E

- 20mm 4-section
- Aluminum
- Three-steps leg opening
- Plastic level-type leg lock

- Load Capacity: 2kg
- A: 1,605mm B: 1,305mm
- 165mm
- 485mm
- 1,360g
- 6183 Q.R.S



## Optional accessories



### Long pan handle for SH-707E

227mm length / 65mm longer than the standard pan handle

## Legs

### MASTER CLASSIC LEG

- 28mm 3-section
- Aluminum



## Heads

### MASTER CLASSIC HEAD

Multi-action head for medium format and 35mm / D-SLR.



	Head attachment screw	Max. operating height	Min. operating height	Folded length	Weight	
MASTER CLASSIC LEG	U1/4	1,500mm	500mm	560mm	1,769g	
	Size of camera platform	Camera mounting screw	Tripod mounting screw	Height	Weight	Load capacity
MASTER CLASSIC HEAD	49x49mm	U1/4	U1/4	130mm	770g	6kg

# SPRINT Series

Designed to travel, designed for photography, designed for the digital era, the SPRINT line of tripods can greatly improve photo by stabilizing your camera, which is critically important for sharp pictures.

## Light Weight & Compact type

-  D-SLR
-  Mirror-less SLR
-  Digital Movie

### Innovative models for digital photography

Designed to travel, designed for photography, designed for the digital era, the SPRINT line of tripods can greatly improve photo by stabilizing your camera, which is critically important for sharp pictures. These all-metal tripods have strength combined with compact size to travel with ease.



**R.F.M. for SPRINT III Series**  
The series introduced well accepted SLIK original R.F.M. (Rapid Flip Mechanism) allows easy leg opening adjustment.

**NEW**

### SPRINT PRO III 3WAY GM / BK

with 3-way pan head SH-704E



20mm 4-section **Aluminum**

Three-steps leg opening Plastic lever-type leg lock

- Load Capacity 2kg
- A: 1,605mm B: 1,305mm
- 165mm
- 475mm
- 1,180g
- 6183 Q.R.S



GM (Gray Metallic)

BK (Black)

**NEW**

### SPRINT PRO III BH GM / BK

with ball head SBH-100DQ



20mm 4-section **Aluminum**

Three-steps leg opening Plastic lever-type leg lock

- Load Capacity 2kg
- A: 1,598mm B: 1,293mm
- 158mm
- 470mm
- 1,020g
- 6252 Q.R.S



GM (Gray Metallic)

BK (Black)

**NEW**

### SPRINT MINI III GM / BK

with ball head SBH-100DQ



20mm 4-section **Aluminum**

Three-steps leg opening Plastic lever-type leg lock

- Load Capacity 2kg
- A: 1,078mm B: 868mm
- 153mm
- 335mm
- 860g
- 6252 Q.R.S



GM (Gray Metallic)

BK (Black)

**NEW**

### VIDEO SPRINT III

with Video head



20mm 4-section **Aluminum**

Three-steps leg opening Plastic lever-type leg lock

- Load Capacity 2kg
- A: 1,600mm B: 1,300mm
- 160mm
- 480mm
- 1,140g
- 6014 Q.R.S



# U Series

Light weight & compact type

Popular, light weight, and an excellent value.  
Easy to operate for both still and video photography.

- D-SLR
- Digital Movie
- Mirror-less SLR
- Compact Camera

**LARGE SIZE LEG OPENING LEVERS**  
Let you adjust tripod height without taking your eye away from the viewfinder.



Quick release shoe for easy mounting and removal of camera or camcorder.



The center column elevation that is easy to get fine adjustment.

## U 9000

2-WAY Leg-Tip

23mm 3-section

Aluminum

Load Capacity 2kg

A: 1,500mm B: 1,200mm

590mm

1,600g

6122 Q.R.S



## U 8000

Won the Good Design

23mm 3-section

Aluminum

Load Capacity 2kg

A: 1,500mm B: 1,200mm

590mm

1,500g

6122 Q.R.S



NEW

## U 874

23mm 4-section

Aluminum

Load Capacity 1.5kg

A: 1,500mm B: 1,240mm

500mm

1,270g

6122 Q.R.S



NEW

## U 873

23mm 3-section

Aluminum

Load Capacity 1.5kg

A: 1,500mm B: 1,177mm

553mm

1,260g

6122 Q.R.S



# COMPACT & MINI Series

Light weight & compact type

The most compact and versatile minipod. Ideal for low position photography and also as a chestpod.

- D-SLR
- Digital Movie
- Mirror-less SLR
- Compact Camera

## COMPACT 8

20mm 4-section

Aluminum

Load Capacity 1kg

A: 1,035mm B: 849mm

365mm

615g



## MINI-PRO 7

20mm 2-section

Aluminum

Load Capacity 2kg

A: 450mm B: 245mm

140mm

195mm

540g

6256N Q.R.S



## MINI-PRO DQ

20mm 2-section

Aluminum

Load Capacity 1kg

A: 226mm B: 181mm

205mm

350g

6252 Q.R.S



## MINI-PRO V

20mm 2-section

Aluminum

Load Capacity 1kg

A: 218mm B: 173mm

200mm

345g



## MINI-8

20mm 2-section

Aluminum

Load Capacity 1kg

A: 210mm B: 164mm

205mm

300g



# MÉMOIRE Series

Mini type

Corresponding to the smartphone and digital camera, as well as video with a detachable smartphone holder.

- Compact Camera

## MÉMOIRE MINI T2

Aluminum

Load Capacity 2kg

52mm

138mm

125g



RD (Red)



GR (Green)



WH (White)



BK (Black)

- D-SLR
- Video Camera
- Digital Movie

## 505QF

with fluid video head 505QF HEAD



28mm 3-section **Aluminum**

5kg	A: 1,640mm B: 1,360mm
750mm	3,600g
6011 Q.R.S	

Best for D-Movie



## 504QF II

with fluid video head 504QF II HEAD



27mm 3-section **Aluminum**

3kg	A: 1,560mm B: 1,295mm
450mm	690mm
2,570g	6027 Q.R.S

Best for D-Movie



**NEW**

## PRO 330 VIDEO

with fluid video head SVH-500



23.4mm 3-section **AMT**  
Aluminum-Magnesium-Titanium Alloy

U1/4-U3/8 Head mounting screw

Three-steps leg opening

Elastic lever-type leg lock

3kg	A: 1,612mm B: 1,262mm
314mm	620mm
1,755g	6502 Q.R.S

Best for D-Movie



**NEW**

## VIDEO SPRINT III

with video head



20mm 4-section **Aluminum**

Three-steps leg opening

Elastic lever-type leg lock

2kg	A: 1,600mm B: 1,300mm
160mm	480mm
1,140g	6014 Q.R.S



## Video heads Designed for video cameras



P.18

### 505QF HEAD

with Quick Release Shoe



P.18

### 504QF II HEAD

with Quick Release Shoe

	Bubble level	Camera mounting screw	Tripod mounting screw	Height	Weight	Load capacity
505QF HEAD	Single bubble level	U1/4	U1/4 · U3/8	100mm	1,200g	5kg
504QF II HEAD	Single bubble level	U1/4	U1/4	105mm	620g	3kg

## High Precision 3-way Pan Heads



### SH-909

Heavy duty construction. 3-way pan head for large format cameras, medium format cameras and 35mm/D-SLR cameras with long telephoto lenses.



### SH-908

Heavy duty construction, just smaller size of SH-909. 3-way pan head for large format cameras, medium format cameras and 35mm/D-SLR cameras with long telephoto lenses.




### SH-807E

with Quick Release Shoe  
High precision 3-way pan head for medium format and 35mm/D-SLR with long telephoto lenses.



### SH-806E

with Quick Release Shoe  
An easy to use pan/tilt head for cameras up to medium format.



	Bubble level	Size of camera platform	Camera mounting screw	Tripod mounting screw	Height	Weight	Load capacity
SH-909	Dual axis bubble level	82x90mm	U1/4 • U3/8	U3/8	140mm	1,710g	12kg
SH-908	Dual axis bubble level	72x71mm	U1/4 • U3/8	U3/8	135mm	1,410g	10kg
SH-807E	Dual axis bubble level plus single bubble level	57x59mm	U1/4	U3/8	150mm	1,000g	10kg
SH-806E	Dual axis bubble level plus single bubble level	57x59mm	U1/4	U1/4	134mm	700g	7kg

## for D-Movie 3-way Pan Heads



These tripods equip special 3-way pan head with oil fluid system.

Pan and tilt frictions are adjusted by knobs easily. These tripods are the best for D-SLR with D-movie, yet suitable for D-SLR camera.

### SH-837HD




### NEW SH-737HD

with Quick Release Shoe



### SH-734HD

with Quick Release Shoe




	Bubble level	Size of camera platform	Camera mounting screw	Tripod mounting screw	Height	Weight	Load capacity
SH-837HD	Dual axis bubble level plus single bubble level	57x76mm	U1/4	U3/8	120mm	1,020g	7kg
SH-737HD	Single bubble level	50x76mm	U1/4	U1/4	105mm	650g	5kg
SH-734HD	Single bubble level	50x76mm	U1/4	U1/4	97mm	540g	3kg

## 3-way Pan Heads




### SH-726E

with Quick Release Shoe  
Compact size 3-way pan head with quick release shoe and a bubble level.




### SH-724E

with Quick Release Shoe  
Compact and light weight 3-way pan head with quick release shoe and a bubble level.




### SH-705E

with Quick Release Shoe  
Compact and light weight 3-way pan head for Carbon Fiber tripods, A.M.T. tripods and others. With convenient omnidirectional quick release shoe.



### SH-704E

with Quick Release Shoe  
Compact and light weight 3-way pan head with convenient quick release shoe.



	Bubble level	Size of camera platform	Camera mounting screw	Tripod mounting screw	Height	Weight	Load capacity
SH-726E	Single bubble level	56x52mm	U1/4	U1/4	104mm	580g	5kg
SH-724E	Single bubble level	50x76mm	U1/4	U1/4	97mm	520g	3kg
SH-705E	—	54x47mm	U1/4	U1/4	90mm	450g	5kg
SH-704E	Single bubble level	48x36mm	U1/4	U1/4	75mm	290g	3kg



## 3-way Pan Heads



### PRO 700DX HEAD

with Quick Release Shoe

Special 4-way pan head – normal 3-way plus movement of round type quick release shoe. Its unique quick release system is one of the fastest and easiest to use in the industry.

6124 Q.R.S.  
6125 Q.R.S.



### ABLE 300DX HEAD

with Quick Release Shoe

The ABLE 300DX Pan Head is solid, precision-machined aluminum. This all-metal head has the strength and durability to handle many DSLRs, mirrorless interchangeable lens cameras (ILCs) and lenses.

6123 Q.R.S.



	Bubble level	Camera mounting screw	Tripod mounting screw	Height	Weight	Load capacity
PRO 700DX HEAD	Dual axis bubble level	U1/4 (U3/8 as option)	U3/8	120mm	1,000g	8kg
ABLE 300DX HEAD	—	U1/4	U1/4	100mm	650g	6kg

## Ball Heads



### SBH-808DQ

Large quick release shoe is designed for sure and easy camera mounting. Independent rotating feature adds to more creative freedom. Friction control system ensures perfect movements against various equipments.

6124 Q.R.S.  
6125 Q.R.S.



### PBH-635AS

ARCA-SWISS  
Compatible Q.R.S.

NEW

6507 Q.R.S.



### PBH-535AS

ARCA-SWISS  
Compatible Q.R.S.

NEW

6507 Q.R.S.



### SBH-200DQ BK

The new SLIK SBH-200 DQ compact ball head is durable and all-metal. It's one-lever operation makes for simple and easy camera movements. In addition, the bubble levels mounted on dual axis make accurate leveling of the camera easy.

6183 Q.R.S.



### SBH-150DQ BK

The SBH-150DQ compact ball head, for monopods and lightweight tripods, features a single lever lock. The lock releases the ball allowing the camera to be positioned at angles and locked into place.

6183 Q.R.S.



### SBH-100DQ BK

The SBH-100DQ BK compact ball head is ultra-light. A single lever locks and releases the ball allowing for a full range of movement. As a result, you can lock the camera in position at almost any angle. The all-metal ball head has a small, low profile quick release plate.

6252 Q.R.S.



	Bubble level	Size of camera platform	Camera mounting screw	Tripod mounting screw	Base diameter	Height	Weight	Load capacity
SBH-808DQ	—	50×50mm	U1/4	U1/4 • U3/8	60mm	120mm	760g	5kg
PBH-635AS	Single bubble level	38×63mm	U1/4	U1/4 • U3/8	56mm	104mm	484g	6kg
PBH-535AS	Single bubble level	38×63mm	U1/4	U1/4 • U3/8	50mm	98mm	378g	5kg
SBH-200DQ BK	Dual axis bubble level	48×36mm	U1/4	U1/4	43mm	87mm	350g	5kg
SBH-150DQ BK	Dual axis bubble level	48×36mm	U1/4	U1/4	37mm	87mm	235g	3kg
SBH-100DQ BK	—	40×30mm	U1/4	U1/4	37mm	68mm	130g	2kg

# Tripod Heads

## Trigger Heads



### AF2100

with Quick Release Shoe



A tripod head that gives you the feeling of 'HAND HELD'. Left hand on the grip, and right hand on the shutter button. Squeeze the trigger to move the camera freely, and let go to lock in. Panoramic shots are easy. Push the little grey switch up, and the camera platform rotates freely. Push down and it's locked. Vertical shots are easy. Just tilt the cut out towards the center ball axis. Winner, The MITI of Japan "Good Design" (G-Mark) award and also, "Long Life" award.



Won the Good Design Long Life Design Award

### AF1100E

with Quick Release Shoe



Simply squeeze the trigger handle to move the head, and let go to lock in any positions. The handle grip makes the ball head feel like more of an extension of your hand than other ball heads available. This trigger style ball head has a bubble level for easy and accurate camera leveling.



	Bubble level	Size of camera platform	Camera mounting screw	Tripod mounting screw	Height	Weight	Load capacity
AF2100	Single bubble level	41x47mm	U1/4	U1/4 · U3/8	140mm	870g	3kg
AF1100E	Single bubble level	48x36mm	U1/4	U1/4 · U3/8	125mm	540g	1.5kg

## Multi Action Heads



These tripods have the unique "Multi-action" head which allows easy operation with a single pan-tilt handle for D-SLR especially. It gives you the opportunity to pan and tilt simultaneously or individually and this permits you to take pictures at any desired angle.

### MASTER CLASSIC HEAD

Multi-action head for medium format and 35mm / D-SLR.



### SH-707E

with Quick Release Shoe



Easy operation with a single pan-tilt handle. Pan and tilt can be operated simultaneously or individually.



	Bubble level	Size of camera platform	Camera mounting screw	Tripod mounting screw	Height	Weight	Load capacity
MASTER CLASSIC HEAD	—	49x49mm	U1/4	U1/4	130mm	770g	6kg
SH-707E	Dual axis bubble level	48x36mm	U1/4	U1/4	81mm	470g	5kg

### Optional accessories

#### Long pan handle for SH-707E

227mm length / 65mm longer than the standard pan handle




## Video Heads



### 505QF HEAD

with Quick Release Shoe




2-way fluid video head. Heavy duty construction for use with any compact to full size video cameras.



### 504QF II HEAD

with Quick Release Shoe



3-way fluid video head for video cameras, also for D-SLR with D-movie.



	Bubble level	Size of camera platform	Camera mounting screw	Tripod mounting screw	Height	Weight	Load capacity
505QF HEAD	Single bubble level	43x52mm	U1/4	U1/4 · U3/8	100mm	1,200g	5kg
504QF II HEAD	Single bubble level	43x79mm	U1/4	U1/4	105mm	620g	3kg


## Special Head for Long Telephoto Lens, Scope & Video



High Precision Shooting Head for scope and video.

### DIGITAL BALANCE PRO

with Quick Release Shoe



152mm range of sliding plate makes easy setting up. Counter spring makes a correction of balance shifting to the leaning to the back or front. Developed for a video camera and a field scope.



#### Concentrating the operating unit to the left side

Both Tilting knob and Panning knob to the left side in order to improve the operability.



#### Coming with a long pan handle

Achieving a smooth motion by spring-balance + oil fluid system. It can be operated with a light force by the long pan handle.

Bubble level	Cam Balancer available weight	Camera mounting screw	Tripod mounting screw	Temperature range
Single bubble level	approx. 1~2kg	U1/4x1	U1/4 · U3/8	-15°C~+50°C

Tilt range	Camera mount plate	Height	Weight	Maximum loading weight
90° (up) and 90° (down)	Rubber	118mm	1,300g	5.0 kg

## Micro Motion Heads



### Ideal pieces for astronomical and timelapse shooting



typical set up for astronomical shooting

#### ASTRA Time-Lapse & Sky Tracker

Motorized turn table for Astronomical and Timelapse shooting

**NEW**

#### ECH-630



The SLIK ASTRA ECH-630 Sky-Tracker is a compact motorized turn table with speed settings for star, moon, and time-lapse photography. Some astro-tracking heads can weigh up to 5kg but the ECH-630 weighs just 630g and takes up about the same amount of room as a 24-70mm lens in your camera bag. This makes it perfect for photographers that hike into remote locations to shoot the stars.

The ECH-630 capacity varies based on its angle. It can hold up 5kg when the turntable is flat and up to 2kg at a 90 degree angle. This makes it perfect for light-weight DSLR cameras or mirrorless cameras with fast prime lenses.

4 high-quality AA sized batteries are all that is needed for the ECH-630 to operate for up to 20 hours of celestial tracking, more than enough for a full night. The unit also has a micro USB port to connect an external battery for even longer run times.

<b>Dimension</b>	D: 84 x W: 86 x H:65mm (exclude protrusions)
<b>Weight</b>	630g (without batteries, cables)
<b>Head Mount Screw</b>	U1/4
<b>Tripod Mounting Screw</b>	U1/4 · U3/8 (double screw adapter)
<b>Max. Load Capacity</b>	at Astronomical Mode: 5 kg at Time-Lapse Mode : 5 kg when the turn table and the ground are close to parallel : 5 kg when the turn table and the ground are close to perpendicular : 2kg (all subject less than 20kg·cm of moment load / about 2kg at 10 cm from rotation axis)

<b>Power</b>	4 AA alkaline batteries (Ni-MH batteries can also be used) DC 5V (micro-USB use together with AA batteries)
<b>Battery Duration</b>	about 20 hours (with alkaline batteries at 20°C)
<b>Operating Temperature</b>	-10°C ~ +40°C (without condensation)
<b>Driving Method</b>	Worm Wheel (by stepping motor)
<b>Astronomical Mode</b>	Star, Moon, Sun & Starscape (0.5x speed) Northern / Southern Hemisphere setting
<b>Time-Lapse Mode</b>	Clockwise, Counterclockwise & Repeat rotation setting Rotation Angle: 5° to 360° (5° increments) or Endless Rotation Speed: 48, 24, 12, 6, 3, 1.5h, 1h, 30min & 15min per one rotation

### MICRO MOTION HEAD

Micro Motion Head for close-up and astronomical shooting

#### **NEW** SMH-250

The SLIK SMH-250 Micro Motion Head that can be used with the "ASTRA" ECH-630 Sky Tracker or any camera or head. This mount allows the ECH-630 to tilt up to 90 degrees and has 4 individual thumb screws for making minute adjustments to the position of the head. This makes finetuning polar alignment of the ECH-630 much easier.

Besides use of sky tracker, the SMH-250 is ideal piece for the macro shooting and the sports optics for fine angle adjustment.

The SMH-250 is all-aluminum and weighs just 250g and takes up little room in a camera bag.

The base of the SMH-250 is Arca-Swiss compatible so it will easily mount into any tripod head with an Arca-Swiss compatible quick release system.



<b>Size</b>	H:37 x W: 88 x D: 46mm
<b>Height Adjustment Angle</b>	20° (±10°)
<b>Pan Adjustment Angle</b>	16° (±8°)
<b>Adjustment Method</b>	Push Screw (1.7" by one full knob rotation)
<b>Weight</b>	250g

<b>Head Mount Screw</b>	U1/4
<b>Tripod Mount Screw</b>	U1/4
<b>Max. Load Capacity</b>	6kg
<b>Accessories</b>	Height adjustment wedge (0 to 90°, 9° pitch)

### Recommendable Legs

#### PRO 400DX LEG



23.4mm  
3-section

**A.M.T.**  
Aluminum Magnesium  
Titanium Alloy



#### PRO 330DX LEG



23.4mm  
4-section

**A.M.T.**  
Aluminum Magnesium  
Titanium Alloy



	Head attachment screw	Max. operating height	Min. operating height	Folded length	Weight
PRO 400DX LEG	U1/4	1,445mm	240mm	580mm	2,070g
PRO 330DX LEG	U1/4	1,502mm	204mm	535mm	1,255g

### Recommendable Heads



#### SBH-200DQ BK

P.17



**NEW**

#### PBH-535AS

P.17

	Bubble level	Size of camera platform	Camera mounting screw	Tripod mounting screw	Height	Weight	Load capacity
SBH-200DQ BK	Dual axis bubble level	48x36mm	U1/4	U1/4	87mm	350g	5kg
PBH-535AS	Single bubble level	38x63mm	U1/4	U1/4·U3/8	98mm	378g	5kg

## Monopods against Vertical Shake

Although a monopod can not stand by itself, it gives you an easy, go anywhere support system for your camera, and eliminates that undesirable vertical movement created when your camera is hand-held.

Your pictures are sharper and clearer. Lighter, and much compact than a tripod, the monopod supports the camera weight, prevents shakes, and lets you focus critically as well as let you shoot at slow shutter speeds.

### STANDPOD 7

with ball head SBH-150DQ

26.8mm  
4-section

A.M.T.  
Aluminum-Magnesium-Titanium alloy

Load Capacity 2kg

955g

6256N Q.R.S

Max. operating height 1,750mm  
Folded length 745mm



### STANDPOD

with 2way Pan Head

26.8mm  
4-section

A.M.T.  
Aluminum-Magnesium-Titanium alloy

Load Capacity 1kg

720g

Max. operating height 1,775mm  
Folded length 720mm



NEW

### PRO POD CF-834

Twist leg lock type

28mm  
4-section Carbon Fiber

500g

Max. operating height 1,629mm  
Folded length 500mm

A.R.S. Anti Rotation System  
Exchangeable leg tips



### PRO POD 600

Lever leg lock type

30.2mm  
4-section A.M.T. Aluminum-Magnesium-Titanium alloy

600g

Max. operating height 1,600mm  
Folded length 535mm



### LIGHTY POD DQ

Lever leg lock type

with ball head SBH-100DQ BK

26.8mm  
5-section A.M.T. Aluminum-Magnesium-Titanium alloy

490g

6252 Q.R.S

Max. operating height 1,615mm  
Folded length 530mm



### LIGHTY POD 200

Lever leg lock type

with ball head SBH-100

23.4mm  
4-section A.M.T. Aluminum-Magnesium-Titanium alloy

380g

Max. operating height 1,585mm  
Folded length 555mm



### LIGHTY POD 100

Lever leg lock type

with ball head SBH-60

20mm  
4-section Aluminum

240g

Max. operating height 1,360mm  
Folded length 435mm



### SLIM POD-X

Lever leg lock type

with 2way Pan Head

20mm  
4-section Aluminum

290g

Max. operating height 1,465mm  
Folded length 500mm



### MONOPOD 350

Lever leg lock type

26.8mm  
4-section A.M.T. Aluminum-Magnesium-Titanium alloy

350g

Max. operating height 1,600mm  
Folded length 510mm



## MAGNESIUM QUICK RELEASE ADAPTER



**DQ-55**  
Weight 108g Width 100mm  
Length 60mm Height 19mm



**DQ-50**  
Weight 103g Width 100mm  
Length 60mm Height 19mm



**DQ-L SHOE**  
Weight 42g Width 75mm  
Length 53mm Height 11mm



**DQ-S SHOE**  
Weight 37g Width 65mm  
Length 53mm Height 11mm

## ALUMINIUM QUICK RELEASE ADAPTER




**DQ-20**  
Dual Axis Bubble Level  
Weight 120g Width 81mm  
Length 57mm Height 20mm



**DQ-10**  
Weight 54g Width 60mm  
Length 38mm Height 15mm

## DOLLY DOLLY II



Folded Length 580mm  
Max. extended diameter 1,020mm  
Height 155mm  
Weight 4,050g

## QUICK RELEASE SHOES / PLATES



ARCA-SWISS  
Compatible Q.R.S.  
**(6505)**

FOR LITE CF-422 /  
LITE CF-522



ARCA-SWISS  
Compatible Q.R.S.  
**(6503) U 1/4  
(6263) U 3/8**

●100mm length  
FOR PRO 724CBH / PRO 634CBH /  
PRO 500BHX / PRO 340BHX /  
PBH-525DS / PBH-425DS



ARCA-SWISS  
Compatible Q.R.S.  
**(6502)**

●70mm length  
FOR PRO 724CBH / PRO 634CBH /  
PRO 500BHX / PRO 340BHX /  
PBH-525DS / PBH-425DS  
LITE-CF522 / LITE-CF422



DIN Standard  
Quick release shoe  
**(6264)**

FOR SH-724E / SH-734HD /  
SH-737HD



DIN Standard  
Quick release shoe  
**(6222)**

FOR GX 6300 / GX 6400



**(6196)**

FOR SH-806E / SH-807E



**(6179)**

FOR DAIWA VT-523



**(6122)**

FOR U 9000 / U 8000 /  
U 7700 / U 6600 /  
U 5500 / U 3300 /  
U 873 / U 874



**(6027)**

FOR VT-551 / PRO 340QF /  
504QF II / 504QF II HEAD



**(6019)**  
FOR AF2100



**NEW**  
ARCA-SWISS  
Compatible Q.R.S.  
**(6507)**

FOR PBH-635AS / PBH-535AS



FOR PRO 823HC /  
ABLE 300HC /  
MINI-PRO 7 /  
**(6256N) STANDPOD 7**



**(6256)**

FOR PRO 724DX / PRO 500HD /  
PRO 340HD / PRO 330HD /  
SH-726E / SH-736HD



**U1/4  
(6124)**

FOR PRO 740DX / PRO 700DX / PRO 740BHX /  
PRO 700BHX / PRO 550BHX / PRO 824CBH /  
SBH-808DQ / PRO 700DX HEAD



**U3/8  
(6125)**

FOR PRO 740DX / PRO 700DX / PRO 740BHX /  
PRO 700BHX / PRO 550BHX / PRO 824CBH /  
SBH-808DQ / PRO 700DX HEAD



**(6123)**

FOR PRO 550DX / PRO 500DX /  
PRO 400DX / PRO 340DX /  
PRO 330DX / ABLE 300DX /  
SH-705E / ABLE 300DX HEAD



FOR LITE AL-420 .M.S / SPRINT PRO II /  
SPRINT MINI II / MINI-PRO DQ /  
LIGHTY POD DQ / SBH-100DQ /  
DQ-10  
**(6252)**



**(6183 BK)**



**(6183 CG)**

FOR PRO 340BH / PRO 330AF / PRO 330EZ / SPRINT PRO EZ /  
SPRINT PRO II 3WAY / SPRINT 150 / SH-704E / SH-707E /  
AF1100E / SBH-150DQ / SBH-200DQ / DQ-20



**(6506)**  
FOR ZF-400 / ZF-300



**(6129)**

FOR BALANCE PRO / 515QF



**(6014)**

FOR 511QF / E-Z POD /  
E-Z POD Jr. / VIDEO SPRINT



**(6011)**  
FOR 505QF /  
505QF HEAD



**(6121)**

FOR 88MB / 444-Sport /  
35DN

## OPTIONAL CENTER COLUMNS

Model / Series	Available tripods
For The Professional series	The Professional, The Professional 4
For Professional II-LE	Professional II-LE & Grand Pro CF4



Exchanging the standard center column and then, you will get lower position.

## SPIKE SET

Exchangeable leg tip set for outdoor use for PRO 900, 800, 700 series Carbon Fiber Tripods



## CARRYING CASES & STRAPS

Carrying Case model	Available tripods	Carrying Case model	Available tripods
Tripod case #2960	up to 960mm folded length tripod	Tripod case #550	up to 550mm folded length tripod
Tripod case #2820	up to 820mm folded length tripod	Tripod case #500	up to 500mm folded length tripod
Tripod case #2770	up to 770mm folded length tripod	Monopod case #2650	up to 650mm folded length monopod
Tripod case #2660	up to 660mm folded length tripod	Strap L	for medium and large tripod
Tripod case #601	up to 600mm folded length tripod	Strap M	for compact tripod



## 11mm THREADED ADAPTER



11mm Thread Adapter is an adapter that converts 3/8 "screw holes into 1/4", Or it converts 1/4" screw to 3/8".



## OTHERS



### LEVELING UNIT 2

Mounted between the head and tripod leg, you can make the leveling easier. Want to rotate the head remains horizontal, necessities of movie shooting. Adopt a rotary lock that does not choose the location of the lock. The adjustment angle is 15°(±7.5°)

Height 34mm Weight 200g Head mounting surface diameter 65mm  
Head mounting screw U1/4 Tripod mounting screw U1/4  
(also available U3/8 by removing the adapter)



### MULTI-ARM 520

Tilting and panning with 2-3 cameras on tripod.

Weight 1,200g  
Length 520mm



### SLIDING ARM II

Horizontal column for mounting on a tripod.  
Tripod mounting screw U1/4 - U3/8  
Base diameter 39mm Slide stroke 370mm  
Weight 530g Length 497mm  
Height 102mm



### CLAMP HEAD

Combination of clamp and camera platform for a variety of use. Available in 3 sizes.



### CLAMP HEAD 32

Weight 400g Length 120mm  
Width 90mm Height 90mm  
Pipe diameter to be mounted 22~32mm

### CLAMP HEAD 38

Weight 500g Length 150mm  
Width 95mm Height 90mm  
Pipe diameter to be mounted 28~38mm

### CLAMP HEAD 45

Weight 500g Length 150mm  
Width 95mm Height 90mm  
Pipe diameter to be mounted 35~45mm

### TWIN CAMERA PLATE 300

Designed for using two cameras, or various accessories on one tripod. TWIN CAMERA PLATE 300 comes with small thread screws, and is more suitable for 35mm/D-SLR cameras.

Weight 500g Length 315mm  
Width 50mm Height 50mm



# LET WELL TAKE ADVANTAGE OF THE TRIPOD

## A variety of shooting that can be what you use a tripod.

By taking the camera on a tripod to release the camera from the "Shaking", it increases the likelihood of further representation. Here we introduce the sense to use a tripod.



### Commemorative photo

Without asking the people around, the photographer goes to the photograph, a tripod is essential. The tripod set can be quickly comfortable, it is useful.



### Shooting of the river flow

You can represent the "Flow" of the river by taking a river in slow shutter speed. In addition, if the shooting by changing the shutter speed remains the same composition, you can also choose a more image as representation.



### Fireworks shooting

To shoot the fireworks, you need to use a slow shutter. In addition, a tripod is required also in the sense of waiting for the chance to predetermine the composition "Chance waiting".



### Shooting of flowers

In the shooting of flowers of close-up, because the magnification is when the depth of field becomes shallow high, the determination of the composition, delicate focusing will be difficult. In addition, it will be slow shutter speed in order to narrow down the deeply take the depth of field. Either by utilizing a tripod, you can shoot remains of feelings.

## How to choose a tripod

"Classification" of the tripod can be determined by the maximum pipe diameter of the legs. The tripod of the class, will introduce an example of equipment that can be place stably. Tripod that corresponds to the D-SLR camera + 70-200mm F2.8 class is a medium-sized tripod of "Pipe diameter around 28mm". Then, D-SLR camera + Double zoom lenses is a small-sized tripod of "Pipe diameter around 24mm".

Pipe diameter 20mm	Travel type tripod for Mirror-less cameras and high-class compact cameras.
Pipe diameter 24mm	Small type tripod for standard zoom, light telescope lens (up to 200mm)
Pipe diameter 28mm	Medium size tripod for 70-200mm F2.8, 70-300mm, etc.
Pipe diameter 32mm	Large size tripod for large-aperture super-telephoto lens 300mm F2.8, etc.
Pipe diameter 38mm	Ultra-large tripod for super telephoto lens with more than 600mm, for studio, etc.


## "Maximum loaded weight" of the tripod

SLIK has decided to "Maximum loaded weight" (\*) in order to use your tripod safely, we regularly review it. It is a numerical value that is determined in order to prevent an accident such as a fall, but do not prevent the occurrence of a blur even in the case of mounting the equipment in this number. For the matching of the tripod and the mounting equipment, you should determine the pipe diameter to the reference.

(\*) It is not simple notation of "Load capacity" that is not take into account the risk only at the maximum weight.

## Determined by the height of the tripod "Angle"

There is a "Angle" – one of the important points when you take a picture. For example, when shooting a sunflower which extends to the height of the eyes, and set up the height of the eye housing, such as "Sample images A" may be visible on captured background. In the "Sample images B", by setting a tripod at lower position with looking up at the Sunflower from "Low Angle", it was the background of the sky. "Sample images C", the camera installed in a high place on a large-size tripod, by taking from the "High Angle", we put the green in the background.



▲ Sample image A



▲ Sample image B




▲ Sample image C

If the tripod height can be set higher, you can shoot Sample Images A to C. But it is limited to an angle that can be taken with the medium and small sized tripods.

## "Low position shooting" for the close-up of the flower.

There is a "Flower pictures" to the popular shooting genre. "The multi-position type" tripod that can set the tripod to a lower position is useful for the shooting of the flowers. Depending on the models, there are – "the type that can be set as it is in the low position", "the type to replace the standard of the center column to an optional shorter center column", "the type that corresponds to the low position by dividing the center column", etc.

In addition, mounting the center column upside-down (Photo-1), or installing a "Clamp Head" in the leg pipe, you can set your camera to a lower position.



At the low position using a short center column



Mounting the center column upside-down (Photo-1)



Using a clamp head (Photo-2) - see page No. 23

## Choose the "Head" according to your shooting purpose.

SLIK offers all kinds of heads for a variety of shooting applications.

### 3-way Pan Head

It is suitable for landscape and still photography. It is characterized by determined the composition carefully. It has been equipped to many of tripods as standard.



SH-807E

### Multi-position Head

SLIK was developed in the 1960s. Suitable for shooting of "Moving things" such as sports, wild animals, wild bird shooting, etc.



SH-707E

### Ball Head

It can be taken in the sense of close to hold by hand. The most problem in using tripod "Determining the composition" can be done as you want.



PBH-535AS

### Trigger Type Head

Free to move and hold the grip and this is a revolutionary trigger type ball head to fix you release. You can use this head of up to 3kg in the sense of "Hand-held feeling".



AF2100 (PAT.)

# Specification Chart

Model	Folded length (mm)	Max. operating height (mm)	Max. center column ext. (mm)	Weight (g)	Max Load weight (kg)	Bubble level	Center column type	Multi position	Leg lock type *	leg tip	How to mount camera **	Page
GRAND PRO CF-4(LEG)	825	2,540	285	3,800	14	—	worm gear	○	T.L.	2WAY	—	04
PRO 924CF(LEG)	554	1,790	310	2,310	10	—	rack & pinion	○	T.L.	RUBBER	—	04
PRO 923CF(LEG)	708	1,900	310	2,320	10	—	rack & pinion	○	T.L.	RUBBER	—	04
PRO CF-834(LEG)	480	1,650	325	1,560	7	—	invertible center column	○	T.L.	RUBBER	—	05
PRO CF-834BH6	566	1,752	325	2,040	6	single	invertible center column	○	T.L.	RUBBER	Q.R.S.	07
PRO CF-833(LEG)	600	1,710	325	1,550	7	—	invertible center column	○	T.L.	RUBBER	—	05
PRO CF-833BH6	686	1,812	325	2,030	6	single	invertible center column	○	T.L.	RUBBER	Q.R.S.	07
PRO CF-734(LEG)	475	1,650	325	1,350	5	—	invertible center column	○	T.L.	RUBBER	—	06
PRO CF-734BH5	557	1,747	325	1,730	5	single	invertible center column	○	T.L.	RUBBER	Q.R.S.	07
PRO CF-733(LEG)	575	1,675	355	1,330	5	—	invertible center column	○	T.L.	RUBBER	—	06
PRO CF-733BH5	657	1,772	355	1,710	5	single	invertible center column	○	T.L.	RUBBER	Q.R.S.	07
PRO CF-634(LEG)	457	1,590	280	930	3	—	invertible center column	○	T.L.	RUBBER	—	06
PRO CF-633(LEG)	540	1,630	390	900	3	—	invertible center column	○	T.L.	RUBBER	—	06
PRO CF-635(LEG)	370	1,310	190	870	3	—	invertible center column	○	T.L.	RUBBER	—	06
LITE CF-522	370	1,466	249	1,113	3	—	invertible center column	○	T.L.	RUBBER	Q.R.S.	08
LITE CF-422	473	1,782	355	1,178	3	—	invertible center column	○	T.L.	RUBBER	Q.R.S.	08
LITE AL-420	428	1,534	225	1,015	2	—	invertible center column	○	L.L.	RUBBER	Q.R.S.	08
LITE AL-420M	358	1,241	171	930	2	—	invertible center column	○	L.L.	RUBBER	Q.R.S.	08
LITE AL-420S	310	1,014	124	785	2	—	invertible center column	○	L.L.	RUBBER	Q.R.S.	08
THE PROFESSIONAL 4	935	2,530	280	6,810	12	dual axis	worm gear	○	T.L.	RUBBER	D.A.L.	09
THE PROFESSIONAL	900	2,000	280	6,210	12	dual axis	worm gear	○	T.L.	RUBBER	D.A.L.	09
PROFESSIONAL II -LE	810	1,835	285	4,810	10	dual axis	worm gear	○	T.L.	RUBBER	D.A.L.	09
PRO 700DX	760	1,900	380	3,670	8	dual axis	invertible center column	○	L.L.	RUBBER	Q.R.S.	10
PRO 700BH6	766	1,882	380	3,150	6	single	invertible center column	○	L.L.	RUBBER	Q.R.S.	10
PRO 500DX	695	1,645	260	2,730	6	—	invertible center column	○	L.L.	RUBBER	Q.R.S.	10
PRO 500BH5	707	1,642	260	2,460	5	single	invertible center column	○	L.L.	RUBBER	Q.R.S.	10
PRO 330DX	600	1,592	350	1,705	3	—	invertible center column	○	L.L.	RUBBER	Q.R.S.	11
PRO 340DX	490	1,440	290	1,625	3	—	invertible center column	○	L.L.	RUBBER	Q.R.S.	11
PRO 340BH	515	1,437	290	1,525	3	dual axis	invertible center column	○	L.L.	RUBBER	Q.R.S.	11
PRO 340BH5	507	1,447	290	1,540	3	single	invertible center column	○	L.L.	RUBBER	Q.R.S.	11
PRO 330AF	660	1,627	350	1,795	1.5	single	invertible center column	○	L.L.	RUBBER	Q.R.S.	11
PRO 400DX	650	1,535	265	2,520	5	—	invertible center column	○	L.L.	RUBBER	Q.R.S.	11
ABLE 300DX	655	1,550	265	2,600	5	—	invertible center column	○	T.L.	RUBBER	Q.R.S.	11
PRO 500 HDII	710	1,650	260	2,730	5	single	invertible center column	○	L.L.	RUBBER	Q.R.S.	12
PRO 340 HDII	507	1,455	290	1,810	3	single	invertible center column	○	L.L.	RUBBER	Q.R.S.	12
PRO 330 HDII	615	1,607	350	1,905	3	single	invertible center column	○	L.L.	RUBBER	Q.R.S.	12
MASTER CLASSIC	650	1,630	135	2,550	6	—	rack & pinion	×	T.L.	RUBBER	D.A.L.	12
PRO 330EZ	600	1,583	350	1,725	3	dual axis	invertible center column	○	L.L.	RUBBER	Q.R.S.	12
SPRINT PRO III EZ	485	1,605	300	1,360	2	dual axis	invertible center column	○	L.L.	RUBBER	Q.R.S.	12
SPRINT PRO III 3WAY GM-BK	475	1,605	300	1,180	2	single	invertible center column	○	L.L.	RUBBER	Q.R.S.	13
SPRINT PRO III BH GM-BK	470	1,598	300	1,020	2	—	invertible center column	○	L.L.	RUBBER	Q.R.S.	13
SPRINT MINI III GM-BK	335	1,078	210	860	2	—	invertible center column	○	L.L.	RUBBER	Q.R.S.	13
VIDEO SPRINT III	480	1,600	300	1,140	2	—	invertible center column	○	L.L.	RUBBER	Q.R.S.	13
U 9000	590	1,500	300	1,600	2	single	rack & pinion	×	L.L.	2WAY	Q.R.S.	14
U 8000	590	1,500	300	1,500	2	—	rack & pinion	×	L.L.	RUBBER	Q.R.S.	14
U 874	500	1,500	260	1,270	1.5	single	rack & pinion	×	L.L.	RUBBER	Q.R.S.	14
U 873	553	1,500	323	1,260	1.5	single	rack & pinion	×	L.L.	RUBBER	Q.R.S.	14
COMPACT 8	365	1,035	186	615	1	—	center column	×	L.L.	RUBBER	S.A.L.	14
MINI-PRO 7	195	450	15	540	2	dual axis	center column	○	L.L.	RUBBER	Q.R.S.	14
MINI-PRO DQ	205	226	45	350	1	—	center column	×	T.L.	RUBBER	Q.R.S.	14
MINI-PRO V	200	218	45	345	1	—	center column	×	T.L.	RUBBER	S.A.L.	14
MINI 8	205	210	46	300	1	—	center column	×	L.L.	RUBBER	S.A.L.	14
MÉMOIRE MINI T2 BK-RD-GR-WH	138	52	—	125	2	—	—	×	—	—	S.A.L.	14
505QF	750	1,640	280	3,600	5	single	rack & pinion	×	T.L.	RUBBER	Q.R.S.	15
504QF II	690	1,560	265	2,570	3	single	invertible center column	○	T.L.	RUBBER	Q.R.S.	15
PRO 330 Video	620	1,612	350	1,755	3	—	invertible center column	○	L.L.	RUBBER	Q.R.S.	15
VIDEO SPRINT III	480	1,600	300	1,140	2	—	invertible center column	○	L.L.	RUBBER	Q.R.S.	15

\* L.L. MEANS LEVER LOCK SYSTEM  
T.L. MEANS TWIST LOCK SYSTEM

\*\* D.A.L. MEANS "DOUBLE ACTION LOCKING SYSTEM"  
S.A.L. MEANS "SINGLE ACTION LOCKING SYSTEM"  
Q.R.S. MEANS "QUICK RELEASE SHOE SYSTEM"

# SLIK®

Designed and engineered in Japan



## SLIK CORPORATION

853 Kayama, Hidaka City,  
Saitama 350-1231, Japan

Phone. 81-42-989-0990

Fax.81-42-989-2444



Slik Corporation reserves the right to make changes in design and / or improvements on the products without any obligation and advanced notice.

© COPYRIGHT 2009 SLIK CORPORATION.

ALL RIGHTS RESERVED. 18/9 J1,500.